Norsat International Inc.

Innovative Communication Solutions

35 YEARS OF EXCELLENCE

LNB
KA-BAND EXT. REF
9000XH

TYPICAL SPECIFICATIONS

Noise figure	1.3 dB
L.O. stability	Phase locked to External Reference
Phase noise (SSB) max	-63 dBc/Hz at 100 Hz -80 dBc/Hz at 1 kHz -92 dBc/Hz at 10 kHz -100 dBc/Hz at 100 kHz
Input VSWR	1.3 : 1
Output VSWR	1.44 : 1

FREQUENCY BANDS AVAILABLE

Typical service	9000XH	
Input frequency (GHz)	20.20 to 21.20	
L.O. frequency (GHz)	L: 19.25	H: 19.20
Output frequency (MHz)	L: 950 to 1950	H: 1000 to 2000

HOW TO ORDER

9000XHCN1-W3

FLANGE HOLES	3 - M3x0.5 4 - 4-40
W - WHITE T - TAN	
POWER REQ.	1 - +9 to + 13V 2 - +18V 3 - +11 to + 28 V
OUTPUT CONNECTOR	N - N Connector
INPUT FREQUENCY	C - 20.20 to 21.20 GHz
FREQUENCY	H - 1000 - 2000 MHz L - 950 - 1950 MHz
EXTERNAL REFERENCE	
LNB SERIES #	

Conversion gain	60 dB
Output P1dB	>3 dBm
Power requirements	+9 to +13 V supplied through center conductor of IF cable (optional +18 V or +11 to + 28 V)
Waveguide Flange	WR42
Current drain	400 mA
Dimensions	120 (L) x 45 (W) x 51(H) mm (2.0 x 1.8 x 3.9 in)
Weight	350 g / 12.3 oz
Temperature Range	-30°C to +55°C
Input Stability	Unconditionally Stable
Gain Flatness	2.5 dB p-p over Full Band
Gain Variation over Temp	±2 dB
External Reference	10 MHz, -3 to +3 dBm
Desensitization	-25 dBm (30 - 31 GHz)
Max Input no damage	0 dBm (20.2 - 21.2 GHz) +10 dBm (30-31 GHz)
Comply to MIL STD	MIL - STD - 188 - 164

MECHANICAL DIAGRAM



Norsat International Inc.

North America +1 800 644 4562

Asia Pacific +1 604 821 2813

Europe, Middle East & Africa +44 1522 730 800

South America +1 604 821 2835

Online sales@norsat.com www.norsat.com

© Copyright 2012 Norsat International Inc. All Rights Reserved. Specifications are subject to change without notice.
Final product may not be as illustrated. The information contained herein does not constitute part of any order or contract.