

# Line Amplifier, L Band Adjustable



Your Trusted Source for Satellite Equipment

- Provides a range of amplification at 950 to 2150 MHz
- Passes L-Band, 10MHz, 22kHz and DC signals with minimal loss
- Handles the current requirement of the LNB
- Rugged die cast aluminum chassis
- Environmentally sealed and moisture resistant



**VS-LAN30**

## TYPICAL SPECIFICATIONS

L-Band frequency range	950 to 2150 MHz	Noise figure maximum	5 dB
L-Band input range	-6 to -30dBm	DC through current maximum	1 A between 12 to 30 V
Conversion gain	6 dB minimum 35 dB maximum	Operating voltage	+12 to +30V
Input VSWR	2.2 : 1	Operating current maximum	175 mA
Output VSWR	2.2 : 1	Dimensions	161 (L) x 85 (W) x 51 (H) mm (6.4 x 3.4 x 2.0 in)
		Weight	500 g / 17.5 oz

VS-LAN30\_REV002

Specifications are subject to change without notice

[sales@vikingsatcom.com](mailto:sales@vikingsatcom.com) • [www.vikingsatcom.com](http://www.vikingsatcom.com)

T: 517.629.3000 • F: 517.629.2379 • 704 North Clark Street • Albion, MI