



Norsat
International Inc.

Innovative Communication Solutions



CFK-200 Communication Suitcase

The Norsat CFK-200 Communication Suitcase is a single case solution that incorporates two Cisco 2811 Integrated Services Routers with Advanced IP services and encryption.



Key Features

The Norsat CFK kits are high performance integrated fly-away kits packaged in two airline carry-on cases, these kits provide secure and non-secure communications via an Ethernet connection. Key features include:

- Full Function Cisco 2811 Routers with Cisco IOS and Advanced IP Services
- Configurable Red and Black Routers with 8 HWIC slots and 2 NME slot
- Supports and stores KG-175 D and KG-250 encryption devices
- Sealed heat exchanger for cooling
- Operates with side covers on
- Custom carbon fiber case with pull handle and wheels
- USB hub, scanner, smart card reader, USB microphone/ headset, Microsoft LifeCam HD-6000 720p HD webcam

Norsat Global Customer Support

All CFK kits are supported by Norsat's global customer support team, who provide assistance for a range of technical issues. Customer support may include installation, training, trouble-shooting, application support, and 24/7/365 support is available to support mission critical applications.



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com

NORSAT CFK-200 COMMUNICATION SUITCASE

INTERFACES

- Up to 16 LAN Fast Ethernet RJ45 Ports with Power Over Ethernet (8 Red/8 Black)
- Up to 8 FXS Ports(4 Red/4 Black)
- 1 WAN Fast Ethernet RJ45 Port
- Up to 8 ISDN BRI Ports (4 Red/4 Black)
- AC Power Input
- 12VDC Output to Power BGAN Terminal
- 2 WWAN interfaces (EVDO, GSM)
- 802.11b/g WiFi Interface
- 1 Courtesy AC Output

COMMUNICATION CAPABILITY

- 802.3af power-over-Ethernet for VoIP support
- Multicast through VPN
- Flash Memory Card
- Supports ISDN, GSM, and CDMA Backhaul
- 802.11b/g Wireless Routing
- Can Dial Two ISDN Channels Simultaneously
- Supports WAN acceleration with Red and Black NME Slots

DETAILED SPECIFICATION

- Dimensions: 22.8"L x 15.8"W x 7.4"H
- Weight: ~37 lbs
- Power Input: 90-220 Volts AC 50/60 Hz
- Operating Temperature: 32° to 113°F (0° to 45°C)
- Storage Temperature: 4° to 149°F (-20° to 65°C)
- Humidity: 5 to 95%, non-condensing
- IP65 Sealed



Norsat
International Inc.

United States
+1 410 263 8165

EMEA
+336 71 38 72 27

Canada and Rest of World
+1 604 821 2800

Toll Free
+1 800 644 4562

Online
sales@norsat.com
www.norsat.com