AUC38 Series

IF/L to C-Band Up Converter

Features

- Compact unit, complete in a single 1 RU package
- Full monitoring and control through LCD and keypad front panel or serial remote
- User selectable spectrum inversion
- Redundant ready
- Available for wide satellite bands
- Flexible design for various user's configurations
- RS232, RS485 and SNMP interface for remote M&C
- Built-in Redundancy control

Reliability

Field proven with system deployed worldwide, Agilis IDU can withstand temperature from 0ºC to +50ºC up to 95% non-condensing humidity.

Quality Assurance

All Agilis IDUs are designed and manufactured according to ISO 9001 Standard.

Agilis

AUC38 Series

IF/L to C-Band Up Converter

Technical Specifications

Output Parameters

Output Frequency	5.85 to 6.750GHz
Impedance	50Ω
VSWR	1.3:1
Output Power @P1dB	+0dBm min

Input Parameters

Input Frequency	950-1825MHz (for L to C) 70 ± 18MHz (for IF to C)
Impedance	50Ω
VSWR	1.5:1
Input Power	-5 to -25dBm

Transfer Parameters

Frequency spectrum	User selectable (for IF to C)
Conversion Gain	28dB min
Gain Adjustment	25dB with 0.5dB step
Gain Flatness	±0.75dB over 36MHz Bandwidth ±2dB over Full Bandwidth
Gain Stability	±0.25dB over 24hours at constant temperature
In Band Spurious	
Carrier dependent	-55dBc at max gain
Carrier Independent	-65dBm max
Out Band Spurious exclude LO	-60dBm max
Third order intermodulation products	40dBc @ two carriers 2MHz apart, 8dB back off from Prated for each carrier
Phase Noise	
@1KHz	-73dBc/Hz
@10KHz	-83dBc/Hz
@100KHz	-93dBc/Hz (for IF to C)
@1KHz	-75dBc/Hz
@10KHz	-85dBc/Hz
@100KHz	-95dBc/Hz (for L to C)

Rear Panel Connections

IF/L Input	BNC Female (for IF to C) N-Type Female (for L to C)
RF Band Output	SMA Female
10MHz Ext REF Connector (Optional)	BNC Female
Remote Connector	DB 9 Female
Power IN	AC/DC

Monitor and Control

Interface	RS232/ RS485/ SNMP (Optional)
Monitoring parameters	LO & Temperature Alarms
Control Parameters	Gain Adjustment @ 0.5dB Step

Power Supply Requirement

AC Input Voltage	100 to 240VAC 50/60Hz
Power Consumption	35W

Environmental

Operating temperature	0ºC to 50ºC
Humidity	up to 95% (Non-condensing)

Mechanical

Dimension	480L x 330W x 44H mm
Weight	3.5kg (for L to C) 4.0kg (for IF to C)

*All specifications are subject to change without notice.
Rev. 300112

www.agilissatcom.com

For more information, please send enquiry to:

Singapore (Headquarters)
mktg_satcoms@stee.stengg.com

USA
usa_satcoms@stee.stengg.com

Europe
europe_satcoms@stee.stengg.com